

S.M. GAUGE C O M P A N Y

sales@pressuregauge.co.uk
www.pressuregauge.co.uk

308-312 Lodge Causeway, Fishponds, Bristol, BS16 3RD
0117 9654615 0117 9583660

63mm Diameter Combined Gauge Pressure & Temperature

Application

Typically used in heating applications and systems where limited space prevents the use of separate pressure and temperature gauges.

Specifically designed for the UK's heating / ventilation, mechanical services and air conditioning markets.



Description

Nominal Size

63mm

Accuracy

± 2.5% fsd Pressure

± 2.0% fsd Temperature

Scales

Top scale bar with blue band

Bottom scale °C with red band

Ranges

0 to 4 bar & 0 to 120 °C

0 to 6 bar & 0 to 120 °C

0 to 10 bar & 0 to 120 °C

Mounting Options

Centre rear entry, direct mount only

Ingress Protection

IP 40

Case

ABS Plastic - Black

Window

Acrylic - Crystal clear, push fit

Pressure Element

CU Alloy - Sealed Bourdon tube C-Type

Temperature Movement

Precision Bimetal Spiral

Pointer

Plastic - Black

Dial

Aluminium - White

Process Connection

Brass - ½" BSPT male with non-return valve

Special Options

Other scales/ranges

Customer logo dials

FULL RANGE OF MATCHING HVAC SPECIFICATION PRESSURE GAUGES AND ACCESSORIES ALSO AVAILABLE

S.M. Gauge Company Ltd, 308/312 Lodge Causeway, Fishponds, Bristol, BS16 3RD

Web. www.pressuregauge.co.uk

Email. sales@pressuregauge.co.uk

Tel. +44 (0) 117 9654615